

TrueTube™ EPS

- Coiled Electropolished Base
- Sulfinert® / Siltek® Lined
- Superior Corrosion Resistance
- World-Class Quality Assurance
- 1/8" - 1/2" and 6mm - 12mm Seamless Tubing



TrueTube EPS

TrueTube EPS provides chromium enriched electropolished 316L stainless steel tubing in continuous coils. It is available in lengths up to 300 feet / 100 meters in sizes from 1/8" to 1/2" and 6mm to 12mm. TrueTube EPS is also internally bonded with a layer of amorphous silicon applied via CVD technology. The proprietary TrueTube EPS silica coating is denser, thicker and more inert than True Tube FS. This combination provides the ultimate in inert stainless steel tubing with improved corrosion resistance and dry-down capabilities at operating temperatures up to 400°C. TrueTube EPS can be provided bare or in O'Brien Analytical's TRACEPAK® and STACKPAK™ heat-traced, insulated tubing bundles.

Specifications

- Seamless 316L SS meets ASTM specifications for consistent physical, dimensional and chemical composition.
- Continuously Electropolished
- Sulfinert / Siltek coating
- Coils are single bagged and packaged to prevent damage during shipment.
- Certificate of Conformance

Part #	Description	Max Length
TD1	1/8" x 0.020" 316L SMLS	100'
TS2	1/4" x 0.035" 316L SMLS	300'
TS3	3/8" x 0.035" 316L SMLS	300'
TS4	1/2" x 0.035" 316L SMLS	300'
EJ4	1/2" x 0.049" 316L SMLS	300'
MTS6	6m x 1mm 316L SMLS	30m
MTS8	8mm x 1mm 316L SMLS	100m
MTS10	10mm x 1mm 316L SMLS	100m
MTS12	12mm x 1mm 316L SMLS	100m
MTJ12	12mm x 1.5mm 316L SMLS	100m

Sulfinert® / Siltek® are registered trademarks of Restek.

Worldwide Offices: