




ATEX Directive



Clamping


ATEX READY SERIES C1				
	part no. XC1_25/80			
	Marking	Temperature	Size	Mounting Pattern
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	$0^{\circ}\text{C} \leq \text{Ta} \leq +50^{\circ}\text{C}$ (T6/T85°C)	Ø25 - Ø80mm	International mount
ATEX READY SERIES C2				
	part no. XC2_50/80			
	Marking	Temperature	Size	Mounting Pattern
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	$0^{\circ}\text{C} \leq \text{Ta} \leq +50^{\circ}\text{C}$ (T6/T85°C)	Ø50 - Ø80mm	NAAMS Standard
ATEX READY SERIES HE1				
	part no. XHE1P0/1/2/3/4			
	Marking	Temperature	Size	Mounting Pattern
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	$0^{\circ}\text{C} \leq \text{Ta} \leq +50^{\circ}\text{C}$ (T6/T85°C)	Ø40 - Ø80mm	International mount
ATEX READY SERIES HE2				
	part no. XHE2P1/2/3			
	Marking	Temperature	Size	Mounting Pattern
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	$0^{\circ}\text{C} \leq \text{Ta} \leq +50^{\circ}\text{C}$ (T6/T85°C)	Ø50 - Ø80mm	NAAMS Standard

ATEX READY **SERIES CX**




part no. XC_X40/50/63			
Marking	Temperature	Size	Mounting Pattern
II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø40 - Ø63mm	International mount / NAAMS Standard

ATEX READY **SERIES CS/HES**




part no. XCS/HES			
Marking	Temperature	Size	Mounting Pattern
II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø40 - Ø80mm	International mount / NAAMS Standard

ATEX READY **SERIES CB**



part no. XCB40/63			
Marking	Temperature	Size	Mounting Pattern
II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø40; Ø63mm	International mount

ATEX READY **SERIES AR**



part no. XAR_/AR_N/AR09R			
Marking	Temperature	Size	Mounting Pattern
II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	12mm; 16mm; 19mm; 22mm; 30mm	International mount / NAAMS Standard

Locating

ATEX READY SERIES R				
	part no. XR_32			
	Marking	Temperature	Size	Stroke
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø32mm	20mm; 40mm
	part no. XR_50/63			
Marking	Temperature	Size	Stroke	
II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø50; Ø63mm	15mm; 25mm; 40mm; 50mm; 60mm	
ATEX READY SERIES RT				
	part no. XRT_40			
	Marking	Temperature	Size	Stroke
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø40 mm	40 mm
ATEX READY SERIES RC				
	part no. XRC_D50/63			
	Marking	Temperature	Size	Stroke
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø50; Ø63mm	25mm; 50mm
ATEX READY SERIES HP				
	part no. XHP50			
	Marking	Temperature	Size	Stroke
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø50mm	15mm; 25mm; 40mm; 50mm; 60mm
ATEX READY SERIES F				
	part no. XF_40/41/63			
	Marking	Temperature	Size	Stroke
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø40 mm, Ø41 mm, Ø63mm	15mm; 25mm; 40mm; 50mm; 60mm
ATEX READY SERIES FT				
	part no. XFT_50			
	Marking	Temperature	Size	Stroke
	II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø50 mm	40mm

Handling

ATEX READY



SERIES J

part no. **XJ_40**

Marking	Temperature	Size	Arm
II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø40 mm	Aluminum / Steel

Pivoting

ATEX READY



SERIES P

part no. **XP63**

Marking	Temperature	Size	Opening Angle
II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø63 mm	0°-135°

cod. **XP80/100/125**

Marking	Temperature	Size	Opening Angle
II 2G Ex h IIC T6 Gb X II 2D Ex h IIIC T85°C Db X	0°C ≤ Ta ≤ +50°C (T6/T85°C)	Ø80, Ø100 mm, Ø125 mm	45°; 60°; 90°; 120°; 135°