

DESCRIPTION

Solenoid valve 3 way
direct acting poppet type

CONSTRUCTION

Body	Brass
Armature tube	Brass
Plunger and core	AISI 430FR
Springs	AISI 302
Seal material	NBR - FPM - EPDM




3

FEATURES

Maximum allowable pressure PS 50bar^③
Maximum fluid viscosity 25cSt (mm²/s)
Ambient temperature: from -10°C to +80°C according to the coil
Universal mounting position

OPTIONS: Manual override
Stainless steel armature tube
Electroless nickel plating
Series 7 explosion proof coil according to ATEX - EExmII
Exhaust port with hosetail connection
cULus certified coils



ON REQUEST: Versions for use with fluid temperature at -40°C

CODE		Connection G	Orifice mm		Kv m³/h	Differential pressure bar			Nominal power			Coil		Seal	Temp. range °C	
①	②		1→2	2→3		Min	Max		AC	VA	DC	Series	Width			
															①	
NC Normally closed															NBR=B	-10 +90
E305A...12///...		1/8"	1.2	1.5	0.04	0	15	15	12	8	6.5	3	22			
E305A...15///...			1.5	1.5	0.06	0	10	10								
E305A...20///...			2	1.7	0.09	0	6	6								
NO Normally open															EPDM=E	-10 +140
E305A...15/S/...		1/8"	1.5	1.5	0.06	0	10	10	12	8	6.5	3	22			
E305A...17/S/...			1.7	2	0.07	0	6	6								
U Universal															FPM=V	-10 +140
E305A...15/G/...		1/8"	1.5	1.5	0.06	0	6	6	12	8	6.5	3	22			

① Seal

② Coil

Example: E305AV15///30B FPM seal

E305AB15/S/301 NBR seal

Coil 24V 50/60Hz, NC


Coil 24V DC, NO

③ The maximum allowable pressure PS for steam 2,5bar (gauge pressure)

COILS ②	Alternating Current 50/60Hz (V)							Direct Current (V)			Electrical connection	Connectors
	12	24	48	110	220 230	240	380	12	24	48		
Series 3 Width 22	30A	30B	30C	30D	30E	30F	30G	300	301	302	DIN 46244	PG9 code 10348000

DESCRIPTION
 Class F insulation
 Voltage tolerance
 AC +15% -10%
 DC ± 10%
 Protection class
 IP65 with connector fitted
 IP00 without connector
 Continuous service ED100%


OPTIONS
 Class H insulation
 Cable attached
 Special coil voltage
 Special coil powers
 cULus certified coils




(for coil details see section 8)

SPARE PARTS LIST

1. Coil fixing nut
2. Coil
3. Plunger
4. Armature tube assembly



MANUAL OVERRIDE



OVERALL DIMENSION

